

A5



A5

- Easy access and simple service of the components.
- Simple operation controls.
- Compact dimensions at the top of the category.
- Operator presence safety system.
- Best scrubbing effect thanks to the floating brush head.
- All around external brush plate for cleaning under the edge.
- Top tanks capacity
- Power cable standard 0,5 m (A5 E)
- **Integrated battery charger** for any type of batteries (A5 B).
- Low level brush/vacuum and traction progressive cut off battery indicator (A5 B).

Optional:

- Code 4.512.0068 15 m. electric cable extension with SCHUKO plug

**With maintenance free
Gel Battery included***

*Version on request:

A5 45T code 8.515.0216 with traction

A5 50T code 8.515.0218 with traction

Technical data:	A5 45E	A5 50E	A5 45*	A5 50*
Code	8.515.3006	8.515.3007	8.515.0206	8.515.0217
power supply	230 V - 50 Hz	230 V - 50 Hz	24 V DC	24 V DC
scrubbing width	450mm	500mm	450mm	500mm
squeegee width	790 mm	790 mm	790 mm	790 mm
max working capacity	1800 m ² /h	2000 m ² /h	1800 m ² /h	2000 m ² /h
detergent tank capacity	44 l.-11.64 gal	44 l.-11.64 gal	44 l.-11.64 gal	44 l.-11.64 gal
recovery tank capacity	50/60 l.	50/60 l.	50/60 l.	50/60 l.
recovery tank capacity	13.22/15.87 gal	13.22/15.87 gal	13.22/15.87 gal	13.22/15.87 gal
traction	mechanical	mechanical	mechanical	mechanical
vacuum motor	1280 mmH ₂ O/480W	1280 mmH ₂ O/480W	1280 mmH ₂ O/480W	1280 mmH ₂ O/480W